

449.00 EUR
incl. 19% VAT, plus [shipping](#)



- INTEL® Bay Trail N2930 SoC Processor (Quad Core, 1.86G)
- Support Dual Gigabit LAN and up to 4 COM ports
- Support up to 2.5" SATA HDD and mSATA card (shared w/ Mini PCI-E)
- Support DVI-I Output
- Total fanless solution in size: 185*142*48mm
- Support +9V~+24V DC-in

| | | |
|--------------------|--------------------------|---------------------------|
| Model Name | JBC375F3A-2930-B | JBC375F3AW-2930-B |
| Part Number | HBJC375F3A-2930-B | HBJC375F3AW-2930-B |

Motherboard Specification

| | | |
|----------------------------------|---|-----------------------|
| CPU | Fanless Intel® Celeron N2930 SoC, 1.83GHz – 2.16GHz Buyrst, Quad-Core, 7.5W TDP/4.5W SDP | |
| Memory | 1 * 204-pin DDR3L-1333 SO-DIMM up to 4GB | |
| VGA | Intel HD Graphics, 313MHz - 854MHz | |
| LAN | 2 * Realtek RTL8111G PCI-E Gigabit LAN | |
| Audio | Realtek ALC662 HD Audio | |
| Storage / Drive Bay | 1 * 2.5" SATA2 3Gb/s drive bay for HDD or SSD 1 * Shared mSATA/mini-PCI Express Combo slot (Full-size) | |
| Wireless / Mini-PCIE Slot | 1 * Mini-PCI Express slot (Half-size) | Wireless 802.11 b/g/n |

| | |
|-------------------------------|--|
| USB | Embedded 1 * USB 3.0 and 5 * USB 2.0 |
| Form Factor | 3.5" SBC (148mm x 102mm) |
| Chassis Specification | |
| Product size | 180 (W) * 142 (D) * 48 (H) mm |
| Color | Black |
| HDD | 1 * 2.5" Hard Disk Drive Bay (Only support SATA 2.5" HDD) |
| Front I/O Port | <ul style="list-style-type: none"> 1 * Power Button 1 * Reset Button 2 * USB 2.0 ports 1 * Line Out Jack 1 * Microphone Jack 4 * RS232 Serial Ports (2 * installed & 2 * cables included in accessory box) 2 * WIFI Antenna holes |
| Rear I/O Port | <ul style="list-style-type: none"> 1 * USB 3.0 ports 3 * USB 2.0 ports 2 * RJ-45 ports 1 * DVI-I port 1 * SMA Connector for WiFi Antenna 1 * Line Out jack 1 * Kensington Lock Hole 1 * +9V ~ +24V DC-in jack |
| Other Internal Headers | <p>These connectors may not be fully usable with chassis closed, but the information is provided for customer alternative uses.</p> <ul style="list-style-type: none"> 1 * USB Headers for up to 2 * USB 2.0 ports 1 * 24-bit dual channel LVDS connector/inverter (CHRONTEL CH7511B chipset up to 1920 x 1200) 1 * Serial Port Header (RS232/422/485) 1 * 8-bit GPIO header 1 * AT/ATX Mode jumper |
| Environment | <p>Operating Temperature : 0 ~ 40°C</p> <p>Storage Temperature : -20 ~ 85°C</p> |
| Standard Accessory | <ul style="list-style-type: none"> - 60W AC-DC Adapter x1 - Power Cord x1 - Wall Mount Kit - DVI-to-VGA adapter x1 - DIN RAIL x2 - CD Disk x1 - Manual x1 - WIFI antenna (with HBJC375F3AW-2930-B model) |
| Functional | Set Top Box, Thin Client, Car Entertainment, Smart Mini PC, POS/POI, KIOSK |
| Packing | <p>Color Box Dimension: 250(W) x 118 (D) x 295 (H) mm</p> <p>Gross Weight■2.2KG</p> <p>Net Weight■1.9KG</p> |
| Certificate | <p>CE,FCC,ErP For Barebone</p> <p>CE,FCC,TUV,UL,CCC,CB,ErP For Power Adapter</p> |