



164.00 EUR
incl. 19% VAT, plus [shipping](#)

- Intel® Celeron™ J1900 (2.0 GHz) quad-core processor
- Support DirectX 11 3D Graphics Acceleration
- Support DDR3L 1333
- Integrated HD Audio CODEC
- Support PCI Express Gigabit LAN
- Support 1*USB3.0 Port
- Support 24-bit Dual channel LVDS
- Onboard 1*MiniPCI-E connector
- Onboard 1 *M- SATA connector
- 2 Phase CPU Power Support
- Support Thunder Protection Function
- [Thin mini ITX](#) Form Factor(170mm X170mm)

CPU-Chipset	• INTEL® Celeron™ J1900 (2.0 GHz) quad-core processor • 2 Phase CPU Power Support
I.O Chipset	• Fintek F71808EC
Memory	• 2*SO-DIMM slot • Support DDR3L 1333 • Max. capacity of system memory up to 16GB

• Expansion Slots	• 1 * MiniPCI-E connector
• Storage	• 1* Serial ATA2 3Gb/s connector(CO-LAY M-SATA) • 1 * M-SATA Connector
• Audio	• ALC887 Audio CODEC • HD Audio CODEC
• Ethernet LAN	• Realtek® RTL8111G Chip • PCI Express Gigabit LAN
• LVDS	• Onboard 24-bit Dual channel
• USB	• 1* USB3.0 (EXT) • 2* USB 2.0/1.1(2 distribute in back panel)
• Special Features	• Support CPU Smart Fan • Support Watch dog Technology • Support GPIO Technology • Support Amplifier function(3W) • Thunder Protection Function • All Solid Capacitor design for CPU
• Back Panel I / O	• 1* PS/2 port • 2* USB 2.0/1.1 ports • 1* USB 3.0 port • 1* RJ-45 port • 1* DVI port • 1* VGA port • 1* 3-JACK
• Internal I / O	• 2*CPU / Chassis Fan connectors • 1*COM header • 1 *24-pin ATX Power connector • 1 *24-bit Dual Channel LVDS header • 1 *GPIO header • 1 *Mini PCI-e connector • 1 * M-SATA Connector • 1* SATA Connector • 1 * Audio header • 1 * Front panel header
• BIOS	• AMI 64MB DIP Flash ROM
• Form Factor	• Thin mini ITX Form Factor(170mm X 170mm)