



999.00 EUR
incl. 19% VAT, plus [shipping](#)

6-Port Gigabit Switch with 4-Port PoE provides the seamless network connection. It integrates 1000Mbps Gigabit Ethernet and 10/100Mbps Fast Ethernet network capabilities.

6 Auto-Negotiation RJ45 ports (port-1 to port-4) of the switch support Power over Ethernet (PoE) function. These PoE ports can automatically detect and supply power with those IEEE 802.3af compliant Powered Devices (PDs). In this situation, the electrical power is transmitted along with data in one single cable allowing you to expand your network where there are no power lines or outlets, where you wish to fix devices such as APs, IP Cameras or IP Phones, etc.

Easy To Use

Easy to install and use. It requires no configuration and installation. With desktop design, outstanding performance and quality, the 6-Port Gigabit Desktop Switch with 4-Port PoE is a great selection for expanding your home or office network.

Key Features:

- * Supports PoE power up to 15.4W for each PoE port
- * Supports PoE power up to 60W for all PoE ports
- * Supports PoE IEEE 802.3af compliant PDs
- * Supports IEEE 802.3x flow control for Full-duplex Mode and backpressure for Half-duplex Mode
- * 4 ports with poe, 1 port 10/100/1000M RJ45 and 1Port Gigabit SFP
- * External power adapter (60W[48V/1.25A])

5 10/100/1000Mbps RJ45 Ports

Interface

1 10/100/1000Mbps SFP Solt
AUTO Negotiation/AUTO MDI/MDIX
10BASE-T: UTP category 3, 4, 5 cable (maximum 100m)
EIA/TIA-568 100Ω STP (maximum 100m)

Network Media

100BASE-TX: UTP category 5, 5e cable (maximum 100m)
EIA/TIA-568 100Ω STP (maximum 100m)
1000BASE-T: UTP category 5, 5e, 6 or above cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m)

Fan Quantity

Fanless

External Power Supply

External Power Adapter(Output: 48VDC /1.25A)

PoE Ports (RJ45)	Standard: 802.3 af/at compliant PoE Ports: Port1- Port 4 Power Supply: 60W
Backbound Bandwidth	10Gbps
Mac Address Table	4K
Dimensions (W x D x H)	(160*90*28 mm)
Transmission Method	Store-And-Forward Compatible With IEEE 802.3af Compliant PDs Priority Function
Advanced Functions	Mac Address Auto-Learning And Auto-Aging EEE802.3x Flow Control 802.1p/DSCP QoS
Certification	CE, FCC, RoHS
Package Contents	Switch, Power Adapter Operating Temperature: 0°C~40°C
Environment	Storage Temperature: -40°C~70°C Operating Humidity: 10% ~ 90% non-condensing Storage Humidity: 5%~90% non-condensing