

589.00 EUR

incl. 19% VAT, plus [shipping](#)

- Intel LGA1200 !



Support: [Datasheet](#)

- Intel® LGA1200 socket 10/11th Gen Core™ Processors
- 2* DDR4 2666/2400MHz SO-DIMM up to 64GB
- 3* USB 3.2 (Type A/Gen2), 1* USB 3.2 (Type C/Gen1), 4* USB2.0, 1* GbE, 1* COM
- 1* HDMI1.4, 1* DP
- DC-19V_120W Adapter

Dimensions	– 264 (W) x 199.4 (D) x 38 (H) mm		
MB model	– MI09-H470 / Mini ITX (6.7-in * 6.7-in, 170 * 170mm)		
Part No	Non-Wifi	Wifi	
	– HBJC511I09-H470-B	– HBJC511I09-H470-B	
CPU/Chipset	– Intel® 10/11th LGA 1200 Socket Core i9/i7/i5/i3/Pentium/Celeron Comet Lake-S/Rocket Lake-S Processor (Max:35W) – Intel® H470 chipset Notes: When the system runs, CPU will automatically adjust its working clock frequency according to changing workload.		
BIOS	– AMI SMT Flash ROM		
Memory	– 2* DDR4 2666/2400MHz SO-DIMM up to 64GB		
Network	– 1* Intel i219V GbE – 1* M.2 E-key Slot 2230 (For WiFi/BT Modul, support CNVi)		
Storage	– 1* 2.5" SATA3 6Gb/s internal drive bay – 1* M.2 M-Key (2260/2280, SATA/PCIe)		
Expansion	– 1* M.2-2230 E-Key (for WIFI, Optional)		
Rear I/O Port	– 3* USB 3.2 (Type A/Gen2) – 1* USB 3.2 (Type C/Gen1) – 1* HDMI 1.4 (Max Resolution: 4096×2160@30Hz) – 1* DP (Max Resolution: 4096×2304@60Hz) – 1* RJ45 (Intel i219V GbE) – 1* COM (RS232) – 1* Line-out, 1* Mic-in – 2* Antenna holes (WiFi only) – 1* DC-In Jack		

Front I/O Port	– 1* Power button, 1* Reset button – 1* Power LED, 1* HDD LED – 1* Line-out, 1* MIC – 4* USB 2.0
Internal I/O Port	– 1* SIM Card holder – 1* M.2-3042 B-Key slot
Power Source	– AC 90~240V input / DC19V_120W output – MI09 MB : 12~19V DC-in
Certification	– CE, FCC, RoHS, ErP Ready
Environment	– Operating Temperature : 0°C~50°C – Storage Temperature : -20°C~70°C – Humidity: 10% ~ 90% RH @40°C (non-condensing)
Packing	– Net Weight■2.4 KG – Gross Weight■3.4 KG – Color Box Dimension■406(W) x 3148(D) x 380(H) mm